

a3

"BRIEF DESCRIPTION OF THE DRAWINGS"

On page 7 after the first line insert as a heading:

a4

"DETAILED DESCRIPTION"

IN THE CLAIMS

Please cancel claims 1-9 and add claim 10 as follows:

~~Sub C. >~~ 10. (New) A turnbuckle device for mutually clamping two concrete shell elements across a joint therebetween, the concrete shell elements each including a frame with longitudinal and transverse struts, said turnbuckle device comprising:

means for retaining said turnbuckle device on one of the longitudinal and transverse struts and positioning said turnbuckle device across abutting edges of the concrete shell elements;

a first lock part including a stationary first claw for engaging one of the frames, the first claw being configured for direct engagement with the respective frame;

a second lock part pivotally disposed with respect to said first lock part and including a second claw configured for direct engagement with another of the frames;

arresting means for limiting a pivoting range of said second lock part in order that the second claw prevents release of the turnbuckle device from the concrete shell element and optimally limits movability of the turnbuckle device.

11. (New) The turnbuckle device according to claim 1 wherein said arresting means is further operable for

2895

enabling the turnbuckle device to be removed for the concrete shell element.

12. (New) The turnbuckle device according to claim 10 or 11 wherein said first lock part comprises comprising stationary first claws and said means for retaining comprises archings, said archings protruding from inner surfaces of the stationary claws.

13. (New) The turnbuckle device according to claim 12 wherein the opposing archings are offset from each other with a distance between the archings being larger than a width of the longitudinal or the transverse strut.

14. (New) The turnbuckle device according to claim 12 wherein the archings are formed oppositely on inner surface of the stationary claws.

15. (New) The turnbuckle device according to claim 10 or 11, wherein the retaining means comprises a shackle which projects from a rod-shaped body which holds and displaceably guides the first lock part, and device further comprises a bolt mounting means for insertion into a first opening in the shackle.

16. (New) The turnbuckle device according to claim 10 or 11 wherein the retaining means comprises a pivoting and/or tilting lever which is disposed on the stationary claws or in the region of the stationary claws.

17. (New) The turnbuckle device according to claim 16 wherein the arresting means comprises a wedge which, being displaced in the direction of force of gravity, blocks the

2895

95
pivotal second claw in a pivoted inner position state and clamps the turnbuckle device for mutual clamping of two concrete shell elements, and when displaced against the force of gravity, releases the pivotal second claw for pivoting and displacement with respect to the first stationary claw.

REMARKS

Amended to the specification and claims is made to conform the application to U.S. practice. No new matter has been added.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "Version with markings to show changes made."

Respectfully submitted,



Walter A. Hackler, Reg. No. 27,792
Attorney of Record
2372 S.E. Bristol - Ste. B.
Newport Beach, CA 92660
(949) 851-5010